

Weather Blocker Instructions

Please read thoroughly before attempting to install your Weather Blocker!

Thank you for your purchase at Carports.com. The weather blocker is exclusively offered at Carports.com! The weather blocker is easy to install, in less than an hour.

IMPORTANT

This is our condensed installation manual. An installation manual that includes photo diagrams is available online by going to www.Carports.com/installation (Free Download - PDF Version)

Please read instructions entirely before starting the installation of your weather blocker.

Tools needed: Scissors, Pliers and One or two helpers!

1. **Remove the weather blocker from the package** and spread it out in a grassy or clean area. Be careful not to walk on, scrape or drag the weather blocker material on the ground or sharp objects. The material can rip or be punctured if not handled carefully.
2. **The weather blocker attaches** to each of the metal legs (framing) on the carport that you have. It attaches at three places on each leg. Once at the top, in the middle, and once at the bottom.
3. Make sure the fabric is somewhat tight, so less adjustment is needed later but not so tight the fabric cannot be moved up and down. The fabric should not sag.
4. **To begin**, start with the last leg on the carport. Carefully slide the zip tie through the weather blocker at the **TOP ONLY** and fasten it tight enough to hold the material but not so tight that you cannot slide the material up and down. Repeat this starting at the top of each leg. Leave a little extra room with the zip tie so that you can adjust accordingly once installed. **DO NOT** skip a leg.
5. **Next** slide the zip tie through the weather blocker at the **BOTTOM ONLY** starting with the last leg. Move forward to each leg after.
6. **Last** slide the zip tie through the middle (half way up) on each leg if preferred or needed. This will secure the weather blocker closely to your carport and keep it from blowing in the wind.
7. **Once completed**, time to clean up and make the weather blocker fit. Move the zip tie as closely as possible to the top or bottom so that it stretches the material as much as possible. This will get out any excess material which would cause it to droop. As you do this for the top and bottom of each leg you will see the weather blocker side(s) take the form of your carport. You may also trim the front and the rear of the weather blocker, to create an even edge beside the metal legs by using household scissors.

Note: The weather blocker material will need to be on your structure for 1-3 days before any wrinkles in the fabric come out. Similar to curtains in your home.

*** The weather blocker can be washed easily using a water hose. (low pressure)

*** If you are enclosing the back or front of your carport, repeat steps 4-5 as necessary. You may find it helpful to draw a diagram of your structure framing and decide where you want to place the zip ties to best fit your needs and how you will be using your structure. You may find it important to place them in different places. It is completely up to you.

*** The weather blocker enclosed sides come “as-is” with no written warranty or guarantee against wind/snow loads, lifetime of product, etc